

High volume hood washer



SH120E

Available in either single or 3 phase options the SH120 EBT is our first High volume pass-through double skinned Hood Washer with an integral break tank. This technically advanced unit has three washing cycles and is capable of handling up to 1200 plates per hour.

Features & Technical Data

- Integral Break Tank
- Rinse aid dispenser
- Detergent pump
- Drain pump
- Wash pump 1100w
- Rack size 500 x 500 mm
- Rack capacity 12-18 plates
- Dimensions mm
W710 x D740 x H1450 lowered
1860 raised
- 3 wash cycles 65, 100 & 150 seconds
- Washing height 850 x 910 mm
- Washing space 500 x 500 x 420 mm
- Tank capacity 42 litres
- Boiler capacity 8.2 litres
- Boiler heating element
Single phase 6000w,
3 phase 9000w
- Tank heating element
Single phase 4000w,
3 phase 4000w
- Wash pump 750w (2.2Bhp)
- Total loading
Single phase 7100w,
3 phase 10100w
- Electrical connection
230V single phase N-50Hz
- Electrical connection
3 phase 400V N-50Hz
- Inlet hose 3/4" G (2-4Bar) flow pressure
- Drain pipe 35mm
- Racks output p/h 55-36-24
- Water consumption 3.5 litres per cycle
- Adjustable feet 30mm
- Packed weight 126kg
- Packed dimensions
700 x 710 x 1510mm
- Class A air gap fully WRAS approved



Serious about Ware Washing!

 **BLUE SEAL**

Unit 6-7 Mount Street Business Park
Mount Street, Birmingham B7 5QU.
Tel: 0121-327-5575 Fax: 0121-327-9711
E mail: sales@blue-seal.co.uk
Website: www.blue-seal.co.uk



WRAS
Approved
CE
Approved



Serious about Ware Washing!



Power, performance and reliability are the hallmarks of the Blue Seal brand and in our line up of Glass and Dishwashers we've developed a range of stylish and robust products that are at the forefront of ware washing technology. There's seven models to choose from, each one capable of handling the requirements of the most demanding environments. From under counter glass washers to high volume pass through hood washers our extensive range has a model for every location. All models are WRAS and CE approved.

So when you're thinking about ware washing - think Blue Seal.

 **BLUE SEAL**



Under counter glass & dishwashers



SG4E

Features & Technical Data

- Rinse aid dispenser
- Detergent pump
- Drain pump
- Rack size 400 x 400mm
- Door height 280mm
- Dimensions W460 x D521 x H680mm
- Wash cycles 120 & 180 seconds
- Water consumption per cycle 2 litres
- Tank capacity 12.5 litres
- Boiler capacity 4 litres
- Boiler heating element 2400w
- Tank heating element 2000w
- Wash pump 220w
- Total loading 3000w
- Electrical connection 230V single phase N-50Hz
- Outlet pipe 28mm
- Inlet hose 3/4" G (2-4Bar) flow pressure
- Pack dimensions 650 x 650 x 760mm
- Packed weight 48kg
- Racks output p/h 20 & 30



SG5E

Features & Technical Data

- Rinse aid dispenser
- Detergent pump
- Drain pump
- Rack size 500 x 500mm
- Door height 330mm
- Dimensions W600 x D600 x H820mm
- Wash cycles 120 & 180 seconds
- Water consumption per cycle 3.5 litres
- Tank capacity 20 litres
- Boiler capacity 7.5 litres
- Boiler heating element 4000w
- Tank heating element 2000w
- Wash pump 750w
- Total loading 4750w
- Electrical connection 230 single phase N-50Hz
- Outlet pipe 31mm
- Inlet hose 3/4" G (2-4Bar) flow pressure
- Pack dimensions 700 x 720 x 900mm
- Packed weight 70kg
- Racks output p/h 20 & 30



SD5E & SD5EBT

Stand alone multi washer



SMW15E

Features & Technical Data

- Rinse aid dispenser
- Detergent pump
- Drain pump
- Rinse pump SD5EBT 200w
- Rack size 500 x 500mm
- Door height 330mm
- Dimensions SD5E W600 x D600 x H820mm, SD5EBT W600 x D620 x H820
- Wash cycle 120 & 180 seconds
- Tank capacity 23.5 litres
- Boiler capacity 7.5 litres
- Boiler heating element SD5E 4000w, SD5EBT 6000w
- Tank heating element 2000w
- Wash pump 750w
- Total loading SD5E 4750w, SD5EBT 6750w
- Electrical connection SD5E 230V single phase N-50Hz, SD5EBT single phase 32 amp
- Outlet pipe 31mm
- Inlet hose 3/4" G (2-4Bar) flow pressure
- Racks output p/h 20 & 30
- Class A air gap fully WRAS approved on SD5EBT

Features & Technical Data

- Rinse aid dispenser
- Detergent pump
- Drain pump
- Rack size 600 x 500mm (26 plates per rack)
- Door height 500mm clearance
- Dimensions W620 x D735 x H1375mm
- 3 wash cycles 60, 120 & 180 seconds
- Tank capacity 35 litres
- Boiler capacity 8.5 litres
- Boiler heating element 6000w
- Tank heating element 3000w
- Wash pump 1500w (2.2Bhp)
- Total loading 7620w 400v 3ph N-50Hz
- Electrical connection 3 phase 400V N-50Hz
- Outlet pipe 35mm
- Inlet hose 3/4" G (2-4Bar) flow pressure
- Racks output p/h 30 -15 -10
- Water consumption 4 litres per cycle

Pass-through hood washer



SH55E

The SH55E Hood Washer is available in single or 3 phase options, has a single wash cycle of 120 seconds and is capable of handling up to 30 racks per hour.

Features & Technical Data

- Rinse aid dispenser
- Detergent pump
- Drain pump
- Rack size 500 x 500mm
- Dimensions mm W710 x D735 x H1450 lowered 1860 raised
- Wash cycle 120 seconds
- Tank capacity 48 litres
- Boiler capacity 8.2 litres
- Boiler heating element 6000w
- Tank heating element 3000w
- Wash pump 750w (2.2Bhp)
- Total loading 6750w
- Electrical connection 230 single phase N-50Hz
- Electrical connection 3 phase 400V N-50Hz
- Inlet hose 3/4" G (2-4Bar) flow pressure
- Drain pipe 35mm
- Racks output p/h 30
- Water consumption 3.5 litres per cycle
- Adjustable feet 30mm
- Packed weight 126kg
- Packed dimensions 700 x 710 x 1510mm

Optional extra

- Stainless steel wings